

Jerrdan MDL 280/110

Specifications and Options

Overreach Capacity

- Retracted at 30° angle 12727kg (28,000lbs)
- Extended at 30° angle 6364kg (14000lbs)
- Maximum reach extended at 0° 1830mm (72")
- Maximum angle 45°
- Maximum height to hook 4445 (175")

Winch Capacity

- Twin 15,000lbs 6820kg variable speed
- Planetary winches c/w air freespool and rope tensioner
- Winch rope Ø11 x 46m (Ø7/16" x 150')
- Twin rotating head sheaves

Underlift Capacity

- Retracted position 1220mm capacity 5000kg (48" 11,000lbs)
- Extended position 1980mm capacity 3865kg (78" 8500lbs)
- Dimension and capacity above relate to centre line of lifting fork
- Lifting capacity with wheel grids 3400kg (7500lbs)
- Lifting capacity with L arms 2270kg (5000lbs)
- Tow rating 11,137kg (24500lbs)
- Power tilt +30° - 10°
- Boom extension 762mm (30")

Accessories Supplied

- 4 sets of forks
- 1 set of spring slippers
- 1 set of fork holders
- 1 set detachable 'L' arms c/w straps & ratchets 2273kg capacity
- 1 set mini bus arms 3400kg capacity
- 1 set alloy steel safety chains
- 1 pair hydraulic rear stiff legs

Locker System

Composite locker system with:-

- (JD14 150A) standard body & 1525 double door crossover and 1 pair stand alone lockers
- Stainless steel door hinges & tee handles
- Gas struts & rubber door seal
- Two way rod lock door closure system
- High flyer

Paintwork

- Underlift and over reach painted in Red.
- Locker system painted in one colour 2 pack acrylic white

Installation

- Equipment installed to chassis PTO & twin gear pump handbrake interlocked
- Load test equipment and certification

Options available

- Upgrade to MDL 320/110
- Wing bars to flyer c/w 1 pair single rotating beacons
- Work lights pair
- 4 Rotator beacon c/w stop tail and indicators 72" optimax

Many other options available on request